

Main Features:



- Input Voltage: 180~528Vac or 250~740Vdc
- Output Wattage: Constant Wattage (C.P.) at **320W** with Adjustable Current Setting
- Programmable Method: Wireless (NFC)
- High Efficiency: Up to **92%**
- Dimming Function: **0-10V with Dim to off (dto)**
- Auxiliaire Voltage: **12Vaux** with **300mA**
- Lightning Protection: Built-in Surge Protector at 10KV/5KA
- Reliability Protection: OVP, SCP, OTP
- Safety Regulation: Complies with UL8750 & EN61347
- **Type TL and HL** Program Certified from UL
- **Class P** UL standard for retrofit kit
- Waterproof Rating: IP67
- Five Year Warranty under Normal Usage Conditions



SPECIFICATION

Model No. ⁽ⁱ⁾	Output Voltage Range	Programmable Output Constant Current Range	OVP	OTP	Case Temperature
	(Vdc)	(mA) ⁽ⁱ⁾	(Vdc max.)	(°C) ⁽ⁱⁱ⁾	(Tc)
LDD-320D229F1400HH-V	137 – 305	1050 – 1400	120% Vo _{max} , typ.	Tc ≥ 105 ± 10°C	90C
LDD-320D152F2100HH-V	91 – 229	1400 – 2100	120% Vo _{max} , typ.	Tc ≥ 105 ± 10°C	90C
LDD-320D114F2800HH-V	69 – 152	2100 – 2800	120% Vo _{max} , typ.	Tc ≥ 105 ± 10°C	90C
LDD-320D076F4200HH-V	46 – 114	2800 – 4200	120% Vo _{max} , typ.	Tc ≥ 105 ± 10°C	90C
LDD-320D046F7000HH-V	27 – 64	5000 – 7000	120% Vo _{max} , typ.	Tc ≥ 105 ± 10°C	90C
Note	(i) Pre-set Constant Current Value with dimming				
	(ii) Lower the output current when Tc ≥ 105 ± 10°C; Auto Recovery When Tc ≤ 70 ± 10°C				

Input Spec.	Condition Description	Min.	Normal	Max.	Units
Input Voltage Range	Dedicated High Voltage Input	180	208-480	528	VAC
Input Frequency Range		47	50/60	63	Hz
Input Current	277 VAC/480 VAC input, full load output			1.3/0.75	A
Power Factor	@60% - 100% load		>0.9		
THD (total harmonic distortion)	@60% - 100% load		<15		%

Inrush Current	At 277 VAC input, 25°C cold start / At 480 VAC input, 25°C cold start			82.8 / 120.4	A
Leakage Current	max @277Vac 60Hz			1.0	mA
Surge Protection	Line to line 6kV, line to ground 10kV, IEC 61000-4-5				

Output Spec.	Condition Description	Min.	Normal	Max.	Units
Current Accuracy			±5		%
Ripple Current	At 100%-60% Load. The result differs according to different LED load characteristic.			5	% Ip-p (Io)
Overshoot/Undershoot	% of Iout max & LED load			10	%
Turn-On Delay	Startup time at cold start			1.2	s
Auxiliary Power (Vaux)	With 300mA max	-5%	12	+5%	Vdc

General Spec.	Condition Description	Min.	Normal	Max.	Units
Efficiency	Measured at full load in the thermal balanced condition		92	93	%
MTBF	measured at Tc= 75°C (MIL-HDBK-217F)		≥280,000		Hours
Lifetime	measured at Tc= 75°C		≥100,000		Hours
Operating/Storage Temperature	10%RH~100%RH (See De-rating Curve for more details)	-40/-40		70/85	°C
Dimension (OL/L x W x H)	OL is the overall length with mounting plates	251/225*68*38.5			mm
		9.88/8.85*2.68*1.51			inch
Weight	Net weight without package	2.54/1.15			lb/kg


Safety & EMC Compliance	Category	Condition Description
Safety Regulations	UL8750	Light Emitting Diode(LED) Equipment for Use in Lighting Products
	UL1012	Power Unit Other Than Class 2
	IEC 61347-1	Lamp Controlgear Part 1: General and Safety Requirements
	IEC 61347-2-13	Lamp Controlgear Part 2-13: Particular Requirement for d.c. or a.c. Supplied Electronic Controlgear for LED Modules
	CE	Europe: EN 61347-1, EN61347-2-13
EMI Standards	IEC 55015	Conducted emission test & Radiated emission test
	IEC 61000-3-2	Harmonic current emissions; Class C (≥75% load)
	IEC 61000-3-3	Voltage fluctuations & flicker
	FCC Part 15	Class B
EMS Standards	IEC 61000-4-2	Electrostatic discharge (ESD)
	IEC 61000-4-3	Radio frequency electromagnetic field susceptibility test (RS)
	IEC 61000-4-4	Electrical fast transient (EFT)
	IEC 61000-4-5	Surge immunity test L-N:2kV; LN-PE:4kV (External Surge Protection Device 4K/6K or 6K/10K)
	IEC 61000-4-6	Conducted radio frequency disturbances test (CS)
	IEC 61000-4-8	Power frequency magnetic field test
	IEC 61000-4-11	Voltage dips

	IEC 61547	Electromagnetic immunity requirements applies to lighting equipment
--	-----------	---

■ Dimming Curve


Parameter	Min.	Typ.	Max.
Vdim Sourcing Current	100uA	150uA	200uA
Vdim Allowed Input Voltage	-20 V		20 V
0-10V Dimming Range	10% (Vdim=1V)	Linear	100% (Vdim=9~10V)
PWM Dimming Range	10% (Duty=10%)	Linear	100% (Duty=90-100%)
Dim off threshold	0.4V or 4%	0.5V or 5%	0.6V or 6%
Dim on threshold	0.6V or 6%	0.7V or 7%	0.8V or 8%
PWM High	3.8V		10V
PWM Low	0V		0.6V
PWM Frequency	300Hz		2kHz
External PWM Controller Current Sinking Capability	300uA		

Dimming Wire




With dim-off (dto)


0-10V Dimming Curve



PWM Dimming Curve




■ **Lifetime vs. Case Temperature**




(End of Life: Maximum Failure Rate=10%)


■ **Power Factor VS Load**




■ THD VS Load



■ Efficient VS Load(2.1A model)



■ Inrush current



Input Voltage	I _{peak}	Duration
277Vac	82.8A	492us
380Vac	100.4A	376us
480Vac	120.4A	356us

■ Dielectric Strength

Unit: Vac	Input	Output	Dimming	Case
Input	-	3920	3920	1960
Output	3920	-	1960	1960


Dimming	3920	1960	-	1960
Case	1960	1960	1960	-

■ Tc Point




Packaging information

Typical Carton Dimension(L×W×H)	490×370×125 mm
Positioning plate	2pcs/carton
Shield Board	1pcs/carton
LED Drivers	8pcs/carton



■ Current vs. Voltage Curve



I_o (mA) V_o (V)	B I_{max} (Rated)	A V_{max} (min I of C.P.)	F (60% of I at A) (as V_{max})	G (as I_{max}) (60% of V at B)	C (as I_{max}) $V_{min} =$ (60% of V at B)	D (10% of I_{max}) (60% of V at B)	E (10% of I at A) (as V_{max})
LDD-320D229F1400HH-V	1400 229	1050 305	630 305	1400 137	1400 137	140 137	105 305
LDD-320D152F2100HH-V	2100 152	1400 229	840 229	2100 91	2100 91	210 91	140 229
LDD-320D114F2800HH-V	2800 114	2100 152	2520 152	2800 69	2800 69	280 69	210 152
LDD-320D076F4200HH-V	4200 76	4200 114	2520 114	4200 60	4200 60	420 60	420 114
LDD-320D046F7000HH-V	7000 46	5000 64	1680 64	7000 46	7000 46	700 46	700 64
On BA Curve Line	Constant Power Area						
Within BAFG Box	Good Performance Area						
Within ABCDE Box	Operational Area						

■ Mechanical Outline (Unit: mm)

Note: Dimensions in millimeters, where 25.4 mm = 1 inch

Tolerance: ± 0.51 mm




Figure 36, AR10PT

Safety Note: Please make sure the output cable does not connect to dimming cable or the cables of other drivers until 20 seconds after being tested because of the remained voltage in the output capacitor.

Revision

Date	Rev.	Description of Change		
		Item	Old	New
12/2/2022	V2a	In Draft Release	/	/