





Input Voltage (V)			347
Max Input Circuit (A)			0.39
Max Output Circuit (A)			0.45
Max. Load(VA)			125
Output Voltage (V)			277
Full Load	EFF. (%)		93
	THD (%)		4.9
	Power Factor		0.983
UL Class B 130 Temp. Code			А
Case Dimension (inches/mm)		L	6.53/166
		W	2.33/59.4
		Н	1.85/47
		М	6/152.4
		А	5.43/138
		S	0.3/7.8
Max Net Weight (lbs)			3.10
Lead Length (i	nches)		8±0.5

Model No.	MTM01253427C-CAN
Product Type	Step-down Transformer
Rating (VA)	125
Vin Vout	347VAC 277VAC
Frequency	60 Hz
Status	Production





*Lead Type: (AVLV2), Type 3321, No. 18 AWG (or Equivalent), rated 150°C, 600 V. Strip 10mm Tin Plated.

Product Standards: UL 5085-1, UL 5085-2

UL CCN: XPTQ2, XPTQ8

Document No.:	PS_MTM_VA0125_34-27_C_CAN_M01
Date:	2017-03-01 (yyyy-mm-dd)

1921 Arena Blvd. • Sacramento • California 95834 • U.S.A • 916- 371-8080 • Fax: 916- 371-6666 • www.mcwonginc.com